

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 013DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb $\leq$ % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles(Porcelain Slabs)

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik A.Ş. Granit Fabrikası Şubesi
Çalca OSB Mah.4 Cad. No :5 Merkez-Kütahya

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	TS EN 14411
Breaking strength	Thickness $\geq$ 7,5mm >1300 N Thickness <7,5mm >700 N	TS EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	TS EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
Resistance to thermal shock	Pass	TS EN 14411
Tactility	NPD	TS EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	$\geq$ 1,0 N/mm ²	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
Durability for:		
- Internal use:	Pass	TS EN 14411
- External use: freeze-thaw resistance	Pass	TS EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Musa YILMAZ / Technical General Manager
Kütahya/TÜRKİYE- 08.05.2026

NG KÜTAHYA SERAMİK A.Ş.
Çalca Mah. Emlakçı Çimen (OSB) Sk. No: 2
Tel: 0 274 227 12 10 Fax: 225 12 13
Çinili V.D. 0 274 227 31 56 KÜTAHYA
Mersis No: 0807027385600015