

**DECLARATION OF PERFORMANCE**  
(According to Regulation EU 305/2011)

No: 003DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Blb % 0,5 < Eb ≤ % 3 (Annex H), Glazed Ceramic Tiles

2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal floor or wall coverings.

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**

NG Kütahya Seramik A.Ş.  
Çalca Mahallesi Ramazan Özen (Osib) Sk.No: 2 Merkez / Kütahya

5. **Name and contact address of the authorized representative:** Not relevant.

6. **System or system of assessment and verification of constancy of performance of the construction product:** System 4

7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. **Declaration of performances concerning a construction product for which a European Technical Assessment has been issued:** Not relevant.

**9. Declared performances:**

| Essential Characteristics                   | Performance                                         | Harmonised Technical Specification |
|---------------------------------------------|-----------------------------------------------------|------------------------------------|
| Reaction to fire                            | A1 <sub>FL</sub> /A1                                | TS EN 14411                        |
| Breaking strength                           | Thickness ≥7,5mm >1100 N<br>Thickness <7,5mm >700 N | TS EN 14411                        |
| Slipperiness <sup>(1)</sup>                 | Refer to the technical documentation or catalog     | TS EN 14411                        |
| <b>Release of dangerous substance, for:</b> |                                                     |                                    |
| - Cadmium                                   | NPD                                                 | TS EN 14411                        |
| - Lead                                      | NPD                                                 | TS EN 14411                        |
| Tactility                                   | NPD                                                 | TS EN 14411                        |
| <b>Bond strength/adhesion, for:</b>         |                                                     |                                    |
| - Cementitious adhesives, Type C2           | ≥ 1,0 N/mm <sup>2</sup>                             | TS EN 14411                        |
| - Reaction resin adhesives                  | NPD                                                 | TS EN 14411                        |
| - Dispersion adhesives                      | NPD                                                 | TS EN 14411                        |
| <b>Durability for:</b>                      |                                                     |                                    |
| - Internal use:                             | Pass                                                | TS EN 14411                        |

Note: (1) where required by regulations

10. **Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

Musa YILMAZ / Technical General Manager  
Kütahya/TÜRKİYE- 08.05.2026

**NG KÜTAHYA SERAMİK A.Ş.**  
Çalca Mah. Ramazan Özen (OSB) Sk. No: 2  
Tel: 0 27 2 225 12 00 Fax: 225 12 13  
Çinili Cad. 07 027 29 56 KÜTAHYA  
Mersis No: 0607 0273 8560 0015