

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex 5)

No: 001DOP-NG

1. **Identification code of the product type:** Used as Indoor Wall Covering Dry Pressed Group BII Eb \leq % 10 (Annex L), Glazed Ceramic Tiles
2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** interior wall covering
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**
NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen Cad.No: 41 Merkez / Kütahya
5. **Name and contact address of the authorized representative :** Not relevant.
6. **System or system of assesment and verification of constancy of performance of the construction product :** System 4
7. **Declaration of performances concerning a construction product covered by a harmonised standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. **Declared performances:**

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|--|------------------------------------|
| Reaction to fire | A1 | TS EN 14411 |
| Breaking strength | Thickness \geq 7,5mm >600 N Thickness <7,5mm >200 N | TS EN 14411 |
| Release of dangerous substance, for: | | |
| - Cadmium | NPD | TS EN 14411 |
| - Lead | NPD | TS EN 14411 |
| Bond strength/adhesion, for: | | |
| - Cementitious adhesives, Type C1 | \geq 0,5 N/mm ² | TS EN 14411 |
| - Reaction resin adhesives | NPD | TS EN 14411 |
| - Dispersion adhesives | NPD | TS EN 14411 |
| Durability for: | | |
| - Internal use: | Pass | TS EN 14411 |

10.Declaration: The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Finans and General Accounting Manager
Kütahya/TURKEY- 21.06.2021

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
Çalca Mah. Ramazan Özen Cad. No:41
Tel: 0 274 225 12 09 Fax: 0 274 225 12 13
Cmhw V.B. No: 207 227 3856 KÜTAHYA
Mersis No: 0607 0273 8550 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 002DOP-NG

- 1. Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb \leq % 0,5 (Annex G), Glazed Ceramic Tiles
- 2. Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal or external floor or wall coverings.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:**
NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen Cad.No: 41 Merkez / Kütahya
- 5. Name and contact address of the authorized representative:** Not relevant.
- 6. System or system of assesment and verification of constancy of performance of the construction product:** System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. Declared performances:

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|---|------------------------------------|
| Reaction to fire | A1 _{FL} /A1 | TS EN 14411 |
| Breaking strength | Thickness \geq 7,5mm >1300 N Thickness <7,5mm >700 N | TS EN 14411 |
| Slipperiness ⁽¹⁾ | Refer to the technical documentation or catalog | TS EN 14411 |
| Release of dangerous substance, for: | | |
| - Cadmium | NPD | TS EN 14411 |
| - Lead | NPD | TS EN 14411 |
| Resistance to thermal shock | Pass | TS EN 14411 |
| Tactility | NPD | TS EN 14411 |
| Bond strength/adhesion, for: | | |
| - Cementitious adhesives, Type C2 | \geq 1,0 N/mm ² | TS EN 14411 |
| - Reaction resin adhesives | NPD | TS EN 14411 |
| - Dispersion adhesives | NPD | TS EN 14411 |
| Durability for: | | |
| - Internal use: | Pass | TS EN 14411 |
| - External use: freeze-thaw resistance | Pass | TS EN 14411 |

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Finans and General Accounting Manager
Kütahya/TURKEY- 21.06.2021

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
Çalca Mah. Ramazan Özen Cad. No:41
Tel: 0 274 225 12 00 Fax: 0 274 225 12 13
Çinli V.D. No: 607 027 3359 KÜTAHYA
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 003DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Blb % 0,5 < Eb ≤ % 3 (Annex H), Glazed Ceramic Tiles
2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal floor or wall coverings.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**
NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen Cad.No: 41 Merkez / Kütahya
5. **Name and contact address of the authorized representative:** Not relevant.
6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4
7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. **Declared performances:**

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|---|------------------------------------|
| Reaction to fire | A1 _{FL} /A1 | TS EN 14411 |
| Breaking strength | Thickness ≥7,5mm >1100 N Thickness <7,5mm >700 N | TS EN 14411 |
| Slipperiness ⁽¹⁾ | Refer to the technical documentation or catalog | TS EN 14411 |
| Release of dangerous substance, for: | | |
| - Cadmium | NPD | TS EN 14411 |
| - Lead | NPD | TS EN 14411 |
| Tactility | NPD | TS EN 14411 |
| Bond strength/adhesion, for: | | |
| - Cementitious adhesives, Type C2 | ≥ 1,0 N/mm ² | TS EN 14411 |
| - Reaction resin adhesives | NPD | TS EN 14411 |
| - Dispersion adhesives | NPD | TS EN 14411 |
| Durability for: | | |
| - Internal use: | Pass | TS EN 14411 |

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Finans and General Accounting Manager
Kütahya/TURKEY- 21.06.2021

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
Çalca Mah. Ramazan Özen Cad. No:41
Tel: 0 274 225 12 00 Fax: 0 274 225 12 13
Çinir Ltd. No.: 607 027 3556 KÜTAHYA
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 004DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb \leq % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi
NG KÜTAHYA SERAMİK
İnköy Mah. 2.Osb 10 Ada 1-2 Parsel Merkez-Kütahya

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---|---|------------------------------------|
| Reaction to fire | A1 _{FL} /A1 | TS EN 14411 |
| Breaking strength | Thickness \geq 7,5mm >1300 N Thickness <7,5mm >700 N | TS EN 14411 |
| Slipperiness ⁽¹⁾ | Refer to the technical documentation or catalog | TS EN 14411 |
| Release of dangerous substance, for: | | |
| - Cadmium | NPD | TS EN 14411 |
| - Lead | NPD | TS EN 14411 |
| Resistance to thermal shock | Pass | TS EN 14411 |
| Tactility | NPD | TS EN 14411 |
| Bond strength/adhesion, for: | | |
| - Cementitious adhesives, Type C2 | \geq 1,0 N/mm ² | TS EN 14411 |
| - Reaction resin adhesives | NPD | TS EN 14411 |
| - Dispersion adhesives | NPD | TS EN 14411 |
| Durability for: | | |
| - Internal use: | Pass | TS EN 14411 |
| - External use: freeze-thaw resistance | Pass | TS EN 14411 |

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Finans and General Accounting Manager
Kütahya/TURKEY- 21.06.2021

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
Çalca Mah. Ramazan Özen Cad. No:41
Tel: 0 274 225 1200 Fax: 0 274 225 12 13
Sicil No: 607 027 3856 KÜTAHYA
Mersis No: 0607 0273 8560 0015