

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011,Annex 5)

No: 005DOP-NG

1. **Identification code of the product type:** Used as Indoor Wall Covering Dry Pressed Group BII Eb
≤ % 10 (Annex L), Glazed Ceramic Tiles

2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** interior wall covering

4. **Name,registered trade name or registered trade mark and contact address of the manufacturer:**

NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen (Osib) Sok.No: 2 Merkez / Kütahya

5. **Name and contact address of the authorized representative:** Not relevant.

6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4

7. **Declaration of performances concerning a construction product covered by a harmonised standard:** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1	EN 14411
Breaking strength	Thickness ≥7,5mm >600 N Thickness <7,5mm >200 N	EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	EN 14411
- Lead	NPD	EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C1	≥ 0,5 N/mm ²	EN 14411
- Reaction resin adhesives	NPD	EN 14411
- Dispersion adhesives	NPD	EN 14411
Durability for:		
- Internal use:	Pass	EN 14411

10.**Declaration:** The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales
Kütahya/TÜRKİYE- 07.10.2022

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mah. Ramazan Özen (OSB) Sk. No:2
Tel: 0 274 225 12 00 Fax: 225 12 13
Cinil V.D. No: 607 027 3856 KÜTAHYA
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011,Annex 5)
No: 006DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb \leq % 0,5 (Annex G), Glazed Ceramic Tiles

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name,registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen (Osib) Sok.No: 2 Merkez / Kütahya

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	EN 14411
Breaking strength	Thickness \geq 7,5mm >1300 N Thickness <7,5mm >700 N	EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	EN 14411
- Lead	NPD	EN 14411
Resistance to thermal shock	Pass	EN 14411
Tactility	NPD	EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	\geq 1,0 N/mm ²	EN 14411
- Reaction resin adhesives	NPD	EN 14411
- Dispersion adhesives	NPD	EN 14411
Durability for:		
- Internal use:	Pass	EN 14411
- External use: freeze-thaw resistance	Pass	EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales
Kütahya/TÜRKİYE- 07.10.2022

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mah. Ramazan Özen (OSB) Sk. No:2
Tel: 0 273 225 12 00 Fax: 225 12 13
Çinir V.D. No: 607 327 3856 KÜTAHYA
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011,Annex 5)

No: 007DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Blb % 0,5 < Eb ≤ % 3 (Annex H), Glazed Ceramic Tiles
2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal floor or wall coverings.
4. **Name,registered trade name or registered trade mark and contact address of the manufacturer:**
NG Kütahya Seramik Porselen Turizm A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mahallesi Ramazan Özen (Osb) Sok.No: 2 Merkez / Kütahya
5. **Name and contact address of the authorized representative:** Not relevant.
6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4
7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.
9. **Declared performances:**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	TS EN 14411
Breaking strength	Thickness ≥7,5mm >1100 N Thickness <7,5mm >700 N	TS EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	TS EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
Tactility	NPD	TS EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	≥ 1,0 N/mm ²	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
Durability for:		
- Internal use:	Pass	TS EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales
Kütahya/TÜRKİYE- 07.10.2022

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mah. Ramazan Özen (OSB) Sk. No:2
Tel: 0 274 225 12 00 Fax: 225 12 13
Sicil V.D. No: 607 037 3856 KÜTAHYA
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011,Annex 5)

No: 008DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group BIa Eb \leq % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi
NG KÜTAHYA SERAMİK
Çalca OSB Mah.4 Cad. No :5 Merkez-Kütahya/ TÜRKİYE

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	EN 14411
Breaking strength	Thickness \geq 7,5mm >1300 N Thickness <7,5mm >700 N	EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	EN 14411
- Lead	NPD	EN 14411
Resistance to thermal shock	Pass	EN 14411
Tactility	NPD	EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	\geq 1,0 N/mm ²	EN 14411
- Reaction resin adhesives	NPD	EN 14411
- Dispersion adhesives	NPD	EN 14411
Durability for:		
- Internal use:	Pass	EN 14411
- External use: freeze-thaw resistance	Pass	EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales
Kütahya/TÜRKİYE- 07.10.2022

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
NG KÜTAHYA SERAMİK
Çalca Mah. Ramazan Özen (OSB) Sk. No:2
Tel: 0 274 225 12 13 Fax: 225 12 13
Cimriye No: 607 027 3856 KÜTAHYA
Mersis No: 0607 0273 8580 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 012DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb \leq % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi
NG KÜTAHYA SERAMİK
Çalca OSB Mah.4 Cad. No :5 Merkez-Kütahya/ TÜRKİYE

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	With Fiberglass Mesh: A2 s1 d0 Without Fiberglass Mesh: A1 _{FL} /A1	TS EN 14411
Modulus of rupture	>45 N/mm ²	TS EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	TS EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
Resistance to thermal shock	Pass	TS EN 14411
Tactility	NPD	TS EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C1	>0,5 N/ mm ²	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
Durability for:		
- Internal use:	Pass	TS EN 14411
- External use: freeze-thaw resistance	Pass	TS EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ahmet DEVECIOĞLU / Technical General Manager
Kütahya/TURKEY- 17.02.2025

NG KÜTAHYA SERAMİK
PORSLEN TURİZM A.Ş.
Çalca OSB Mah.4 Cad. No:5 Merkez-Kütahya
T.C. 067 027 3856 KÜTAHYA
Mersis No: 0607 0273 8500 0015

DECLARATION OF PERFORMANCE
(According to Regulation EU 305/2011, Annex V)

No: 013DOP-NG

1. Identification code of the product type: Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb \leq % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles(Porcelain Slabs)

2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date

3. Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi
NG KÜTAHYA SERAMİK
Çalca OSB Mah.4 Cad. No :5 Merkez-Kütahya/ TÜRKİYE

5. Name and contact address of the authorized representative: Not relevant.

6. System or system of assesment and verification of constancy of performance of the construction product: System 4

7. Declaration of performances concerning a construction product covered by a harmonised Standard : NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	TS EN 14411
Breaking strength	Thickness \geq 7,5mm >1300 N Thickness <7,5mm >700 N	TS EN 14411
Slipperiness ⁽¹⁾	Refer to the technical documentation or catalog	TS EN 14411
Release of dangerous substance, for:		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
Resistance to thermal shock	Pass	TS EN 14411
Tactility	NPD	TS EN 14411
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	\geq 1,0 N/mm ²	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
Durability for:		
- Internal use:	Pass	TS EN 14411
- External use: freeze-thaw resistance	Pass	TS EN 14411

Note: (1) where required by regulations

10.Declaration: The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ahmet DEVECIOĞLU / Technical General Manager
Kütahya-TURKEY- 17.02/2025

NG KÜTAHYA SERAMİK
PORSELEN TURİZM A.Ş.
Çalca Mah. Ramazan Özen (OSB) SK. No:2
Tel: 0 274 225 12 00 Fax: 225 12 13
Cinn. V.D. No: 607 027 3856 KÜTAHYA
Mersis No: 0807 0273 8560 0015